

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING



#### 1.1. Product identifier

Product name: OWATROL PREPDECK

Product code: PREP01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Stripper / Cleaner for exterior woods

# 1.3. Details of the supplier of the safety data sheet

Registered company name: DURIEU S.A..

Address: Z.A.I. "La Marinière" 2,bis rue Charles de Gaulle.91070.BONDOUFLE.FRANCE.

Telephone: +33 (0)1.60.86.48.70. Fax: +33 (0)1.60.86.84.84.

info@durieu.com www.durieu.com



# 1.4. Emergency telephone number: + 33 (0)1.45.42.59.59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

# **SECTION 2: HAZARDS IDENTIFICATION**

# 2.1. Classification of the substance or mixture



## In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.



# In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Corrosive (C, R 35).

May produce an allergic reaction.

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

## 2.2. Label elements



# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS05

Signal Word : DANGER

Product identifiers :

011-002-00-6 SODIUM HYDROXIDE

Additional labeling :

EUH208 Contains TERPENES D'ORANGE. May produce an allergic reaction.

Hazard statements :

H314 Causes severe skin burns and eye damage.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.



# 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures



#### Composition:

Identification	(EC) 1272/2008	67/548/EEC	Note	%
NDEX: 603-057-00-5	GHS07	Xn		2.5 <= x % < 10
CAS: 100-51-6	Wng	Xn;R20/22		
EC: 202-859-9	Acute Tox. 4, H332			
REACH:	Acute Tox. 4, H302			
01-2119492630-38				
BENZYL ALCOHOL				
INDEX: 011-002-00-6	GHS05	С	[1]	2.5 <= x % < 10
CAS: 1310-73-2	Dgr	C;R35		
EC: 215-185-5	Skin Corr. 1A, H314			
SODIUM HYDROXIDE				
INDEX: 008			[1]	2.5 <= x % < 10
CAS: 34590-94-8				
EC: 252-104-2				
(2-METHOXYMETHYLETH	0			
XY)PROPANOL				
INDEX: 094	GHS07, GHS09, GHS08,	Xn,N		0 <= x % < 0.05
CAS: 8028-48-6	GHS02	Xn;R65		
EC: 232-433-8	Dgr	Xi;R38-R43		
	Flam. Liq. 3, H226	N;R51/53		
TERPENES D'ORANGE	Asp. Tox. 1, H304	R10		
	Skin Irrit. 2, H315			
	Skin Sens. 1, H317			
	Aquatic Chronic 2,			
	H411			

# Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

# **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

## 4.1. Description of first aid measures



# In the event of exposure by inhalation:

In the event of an allergic reaction, seek medical attention.

# In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.



# In the event of splashes or contact with skin:

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

## In the event of swallowing:

Do not give the patient anything orally.

Seek medical attention immediately, showing the label.

In case of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

In case of accidental ingestion, call a doctor to assess the appropriateness of monitoring and subsequent treatment in hospital, if necessary.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### **SECTION 5: FIREFIGHTING MEASURES**

This product is not classed as flammable.

#### 5.1. Extinguishing media

## Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

CO2, extinguishing powder or pulverized water.

#### Unsuitable methods of extinction

Direct water iet.



#### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

Smoke and vapors, carbon oxides, incomplete combustion products.

## 5.3. Advice for firefighters

Boot, gloves and glasses.

Bring independant breathing apparatus.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.



# For non first aid worker

Avoid any contact with the skin and eyes.



# For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

# 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

# 6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

## 6.4. Reference to other sections

No data available.

# **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Keep containers tightly closed.

#### Fire prevention:

Prevent access by unauthorised personnel.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Containers which are opened must be carefully resealed and kept upright.

#### Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep only in the original container

Part used containers must be properly closed and kept in upright position.

Keep away from corrosive agents such as strong acids or alkalines to avoid possible leakage or self combustion.

Keep container tighly closed in a dry place.

Stock between +5°C and +30°C in a dry, well ventilated place.

#### Storage

Keep out of reach of children.

Keep container tightly closed in a dry, well ventilated place.

The floor must be impermeable and form a collecting basin so that, in case of accidental spillage, the liquid can not spread beyond.

VLE-mg/m3:

VLE-ppm:

Notes

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

## 8.1. Control parameters



CAS

## Occupational exposure limits:

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

VME-ppm:

34590-94-8	308	50	-	-	Peau		
- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):							
CAS TWA: STEL: Ceiling: Definition: Criteria:							
1310-73-2	_	_	2 mg/m3	_	_		

34590-94-8 150 ppm 100 ppm ACM (BAHA TROS 000 24/06/2010) :

VME-mg/m3:

- Germany - AGW (BAUA - 1103 300, 21/00/2010).								
CAS	VME :	VME :	Excess	Notes				
34590-94-8	50 ml/m3	310 mg/m3	1(1)	DEG EU				

- France (INRS - ED984 :2008) :

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
1310-73-2	-	2	-	-	-	-
34590-94-8	50	308	-	-	*	84

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA:	STEL:	Ceiling :	Definition :	Criteria :
1310-73-2	-	2 mg/m3	-	-	-
34590-94-8	50 ppm	-	-	-	-

# 8.2. Exposure controls



# Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

## - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties:

- Impervious gloves in accordance with standard EN374

Permeability time: >480 min for a thickness >0.75 mm

CEN recommendations: EN 420 and EN 374/3

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Suitable type of protective boots:

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

## - Respiratory protection

Type of FFP mask :

Wear a disposable half-mask dust filter in accordance with standard EN149.

Category:

- FFP2

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- A2 (Brown)
- B2 (Grey)

Particle filter according to standard EN143:

- P2 (White)

CEN recommendations: EN 136, EN 140, EN 405 for masks and EN 143, EN 149 for filters.

Respiratory protective gears to absorb the aerosols must be carried when the product is sprinkled insofar as the exposure cannot be controlled to be in lower part of the limiting risk of exposure.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

# General information :

Physical state :	Fluid liquid.
Colour:	Amber

Important health, safety an	d environmental ir	nformation
-----------------------------	--------------------	------------

pH:	13.00 .
	Strongly basic.
Boiling point/boiling range :	Not specified.
Flash point interval :	Not relevant.
Vapour pressure (50°C):	Not relevant.
Density:	>1
Water solubility :	Dilutable.
Viscosity:	70 cSt (23°C)

OWATROL PREPDECK - PREP01	EACH) Version 12.1 (25-03-2015) - Page 6/9
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not specified.
9.2. Other information	
VOC (g/l):	182

# **SECTION 10: STABILITY AND REACTIVITY**

Shake product well before using.

#### 10.1. Reactivity

No data available.

## 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

Avoid:

- frost

Keep away from corrosive agents such as strong acids or alkalines to avoid possible leakage or self combustion.

Always stock in its original packaging. Do not transfer in another package.

#### 10.5. Incompatible materials

Acids and oxidizing agents.

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

## 11.1.1. Substances

No toxicological data available for the substances.

# 11.1.2. Mixture

## Skin corrosion/skin irritation:

Corrosive classification is based on an extreme pH value.



# $\label{lem:Respiratory} \textbf{Respiratory or skin sensitisation:}$

Contains at least one sensitising substance. May cause an allergic reaction.

# Other information

Formula sent to the I.N.R.S.

# **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

Probably low dangerous to aquatic organisms

Do not leave this product, not diluted or in great quantity, penetrate the ground water, waters or the drains.

## 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

# 12.2. Persistence and degradability

Biodegradable

# 12.3. Bioaccumulative potential

No data available.

# 12.4. Mobility in soil

This product is dilutable in water in all proportion.

# 12.5. Results of PBT and vPvB assessment

No data available.

# 12.6. Other adverse effects

No data available.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

## 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.



# Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

15 01 10 \* packaging containing residues of or contaminated by dangerous substances

06 02 04 \* sodium and potassium hydroxide



# SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

#### 14.1. UN number

1719

# 14.2. UN proper shipping name

UN1719=CAUSTIC ALKALI LIQUID, N.O.S.

(sodium hydroxide)

# 14.3. Transport hazard class(es)

- Classification :



8

# 14.4. Packing group

П

# 14.5. Environmental hazards

.

# 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C5	II	8	80	1 L	274	E2	2	E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			-
	8	-	II	1 L	F-A,S-B	274	E2			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	8	-	II .	851	1 L	855	30 L	A3 A803	E2	
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

# 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

# **SECTION 15: REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



# - Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
  - Directive 1999/45/EC and its adaptations
  - EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
  - EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
  - EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
  - EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

#### - Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3). Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

#### - Particular provisions :

No data available.

## 15.2. Chemical safety assessment

No data available

#### **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.



In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols:



Corrosive

Contains:

011-002-00-6 SODIUM HYDROXIDE

Contains EC 232-433-8

Causes severe burns.

Risk phrase : R 35

Safety phrase :

S 1/2 Keep locked up and out of the reach of children.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

TERPENES D'ORANGE. May produce an allergic reaction.

S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible).

S 25 Avoid contact with eyes.

S 27 Take off immediately all contaminated clothing.

S 28 After contact with skin, wash immediately with plenty of clean water S 64 If swallowed, rinse mouth with water (only if the person is conscious).

S 20 When using do not eat or drink.



# Title for H, EUH and R indications mentioned in section 3 :

Flammable liquid and vapour.
Harmful if swallowed.
May be fatal if swallowed and enters airways.
Causes severe skin burns and eye damage.
Causes skin irritation.
May cause an allergic skin reaction.
Harmful if inhaled.
Toxic to aquatic life with long lasting effects.
Flammable.
Harmful by inhalation and if swallowed.
Causes severe burns.
Irritating to skin.
May cause sensitisation by skin contact.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Harmful: may cause lung damage if swallowed.

# Abbreviations:

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS05 : Corrosion