

# FLOOD® PRO SERIES

FLD51

## Wood Cleaner

#### **GENERAL DESCRIPTION**

**FLOOD** Pro Series Wood Cleaner is a unique, premium quality product for restoring the clean, refreshed look to exterior wood and other surfaces. It cleans stains caused by mildew, dirt, algae and mold without scrubbing. Unlike bleach alone, **FLOOD** Pro Series Wood Cleaner works on the surface to lift dirt that can then be rinsed away. This product contains no phosphates, acids, solvents or petroleum distillates. When used as directed, it will not harm most plants, pets or fish.

### **RECOMMENDED USES**

Use on decks, wood siding, shakes, shingles, and fences. Also recommended for use on concrete, brick, stucco, tile, and vinyl. Use of this product may return the original green color to pressure treated wood. Application of this product may cause a fuzzy appearance to wood previously damaged by pressure washing or excessive weathering. Application to new wood or newly sealed wood may cause spotting and discoloration. May cause redwood to darken. Test in a small inconspicuous area and let dry before application.

### PRODUCT INFORMATION

FLD51

#### **PACKAGING**

2.5 - Gallon (9.46 L)

### PRODUCT DATA

**PRODUCT TYPE**: Sodium Hypochlorite Solution

**WEIGHT/GALLON:** 8.9 lbs. (4.1 kg) +/- 0.2 lbs. (91 g)

**COVERAGE:** One gallon (3.78 liters) will clean approximately 250-300 sq. ft. (23.2-27.9 sq. meters). Coverage will vary depending on type, age and texture of wood.

**RECOMMENDED SPRAY EQUIPMENT**: Use a plastic, pump-style garden sprayer and hose.

**CLEANUP:** Rinse tools and spray equipment thoroughly with water.

**STORAGE**: Store in a cool dry location in tightly closed plastic container. Avoid exposure to sunlight. Do not reuse container. Rinse container thoroughly before disposal.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

### **FEATURES**

Ready to use

Works in 5-10 minutes

No scrubbing required, just rinse away

Removes 4X more dirt than water alone

Removes stains from mold, mildew and algae

FLOOD PRO SERIES

### Wood Cleaner

#### DIRECTIONS FOR INTERIOR AND EXTERIOR USE

AREA PREPARATION: Spray all plants and vegetation liberally with water before and after application. Cover delicate vegetation to avoid damage. Do not allow to come in contact with metal, fabric, floor coverings, or lawn furniture.

SAFETY PRECAUTIONS: Wear chemical resistant gloves, safety goggles and protective clothing. Do not mix with any other chemicals or other household cleaning products as hazardous fumes may result. Surfaces are slippery when wet. Use caution when walking on wet surfaces during application.

APPLICATION: Surfaces to be cleaned must be thoroughly dry. FLOOD Pro Series Wood Cleaner should be applied at full strength with spray equipment recommended below. When treating vertical surfaces, apply from bottom to top. Spray the affected area liberally and allow to stand for 5-10 minutes. NO SCRUBBING NECESSARY. Cleaning action will occur within minutes. Thoroughly rinse treated surface and surrounding areas with large amounts of water to neutralize cleansing action. A second application may be applied if necessary.

FOR PERIODIC CLEANING OF COMPOSITE DECKING: Apply FLOOD Pro Series Wood Cleaner liberally and work into surface with a stiff broom (slight foaming should be seen, it not apply more cleaner). Rinse, let dry, apply a second application if needed. Slight yellowing of the deck is normal and will fade in a matter of days.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

### LIMITATIONS OF USE

KEEP IN AN UPRIGHT POSITION. PROTECT FROM FREEZING.

### **PRECAUTIONS**

### DANGER! CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT IRRITA-

TION. The product may not be stable under certain conditions of storage or use: high temperature/pressure hazard. Oxidizer. Contact with combustible material may cause fire. This material increases the risk of fire and may aid combustion. Can enter lungs and cause damage. Keep away from clothing and other combustible materials. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information. FIRST AID: If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. Call physician immediately. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. FLOOD and the FLOOD and Paintbrush Design are registered trademarks of PPG Industries, Inc. © 2015 PPG Industries, Inc. All Rights Reserved.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc. Architectural Coatings One PPG Place Pittsburgh, PA 15272 www flood com

**Technical Services** 

Architect/Specifier 1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc. 2505, rue de la Métropole, Longueuil (Québec) Canada J4G 1E5

T.D. FLD51 1/2016

