

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 31/10/2018 Revision date: 08/03/2021 Supersedes version of: 31/10/2018 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: CHALK FINISH
UFI	: PEH0-K03Q-T00Y-5PP4
Product code	: CHALK
Vaporizer	: Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public Use of the substance/mixture

: Spraying paint (spray can)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Novasol Spray, S.A. P.I.: Empalme - C/ Empalme, 27 43712 Llorenç del Penedès - Spain T +34 977 677 305 - F +34 977 678 072 novasol@novasolspray.com - www.novasolspray.com

1.4. Emergency telephone number

Emergency number

: +34 977 677 305 Office hours: Monday-Friday 8:30 AM-6:00 PM GMT+1

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 Serious eye damage/eye irritation, Category 2 Full text of H statements : see section 16 H222;H229 H319

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/	(2008 [CLP]
Hazard pictograms (CLP)	GHS02 GHS07
Signal word (CLP)	: Danger
Hazard statements (CLP)	: H222 - Extremely flammable aerosol.
	H229 - Pressurised container: May burst if heated.
	H319 - Causes serious eye irritation.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand.
	P102 - Keep out of reach of children.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
	P264 - Wash hands, forearms and face thoroughly after handling.
	P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
EUH-statements	: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not
	breathe spray or mist.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether (Aerosol propellants) substance with a Community workplace exposure limit (Note U)	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128- 37	≥ 50 – < 80	Flam. Gas 1A, H220 Press. Gas
propan-2-ol; isopropyl alcohol; isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	≥ 15 – < 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 $\mu m]$	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-002 REACH-no: 01-2119489379- 17	≥5-<7	Carc. 2, H351
Reaction mass of ethyl benzene and xylene	EC-No.: 905-588-0	≥ 0,1 – < 3	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H-statements: see section 16

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	 Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water.
First-aid measures after eye contact	: If eye irritation persists: Get medical advice/attention. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and effe	ects, both acute and delayed
Symptoms/effects after eye contact	: Causes serious eye irritation. Eye irritation.
4.3. Indication of any immediate medic	al attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Sand. Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.
5.2. Special hazards arising from the subst	ance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic fumes may be released.
5.3. Advice for firefighters	
Firefighting instructions Protection during firefighting	 Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures	
6.1. Personal precautions, protective	equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.
6.2. Environmental precautions	

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up		
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Mechanically recover the product. Notify authorities if product enters sewers or public waters.	
Other information	: Dispose of materials or solid residues at an authorized site.	
6.4. Reference to other sections		

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includi	ing any incompatibilities
Storage conditions Incompatible products Incompatible materials	 Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep cool. Strong bases. Strong acids. Sources of ignition. Direct sunlight.
7.3. Specific end use(s)	

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

dimethyl ether (115-10-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Dimethylether
IOEL TWA	1920 mg/m ³
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Chemical goggles or safety glasses. eye protection (EN166)

8.2.2.2. Skin protection

Hand protection: Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection: If vapour is released : Disposable half mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Colour Odour Odour Odour threshold pH Relative evaporation rate (butylacetate=1) Melting point Freezing point Boiling point Flash point Auto-ignition temperature Decomposition temperature Flammability (solid, gas) Vapour pressure Relative vapour density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Viscosity, kinematic Viscosity, dynamic	 Liquid Various. characteristic. No data available -25 °C Aerosol jet -41 °C Aerosol jet No data available
Explosive properties	: Pressurised container: May burst if heated.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Oxidising properties Explosive limits	 No data available No data available
9.2. Other information	
Not volatile VOC content VOC content	: 20,6 wt% : 69,5 wt% : 637 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability
Not established.
10.3. Possibility of hazardous reactions
Not established.
10.4. Conditions to avoid
Direct sunlight. Extremely high or low temperatures. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral):Acute toxicity (dermal):Acute toxicity (inhalation):	Not classified Not classified Not classified
dimethyl ether (115-10-6)	
LC50 Inhalation - Rat [ppm]	164000 ppm Animal: rat, Animal sex: male, 95% CL: 142000 - 203000
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
LD50 oral rat	 > 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 oral	> 10000 mg/kg
LD50 dermal	> 10000 mg/kg
LC50 Inhalation - Rat	> 6,8 mg/l/4h
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)
LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Reaction mass of ethyl benzene and xylene	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
Skin corrosion/irritation:Additional information:	Not classified Based on available data, the classification criteria are not met

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity Additional information	 Not classified Based on available data, the classification criteria are not met
	g 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
IARC group	2B - Possibly carcinogenic to humans
propan-2-ol; isopropyl alcohol; isopropano	l (67-63-0)
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
propan-2-ol; isopropyl alcohol; isopropano	l (67-63-0)
STOT-single exposure	May cause drowsiness or dizziness.
Reaction mass of ethyl benzene and xylene	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reaction mass of ethyl benzene and xylene	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
CHALK FINISH	
Vaporizer	Aerosol
Potential adverse human health effects and	: Based on available data, the classification criteria are not met
symptoms	

SECTION 12: Ecological information	
12.1. Toxicity	
	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term : (acute)	Not classified
Hazardous to the aquatic environment, long-term : (chronic)	Not classified
dimethyl ether (115-10-6)	
LC50 96h fish (1)	> 4,1 g/l Test organisms (species): Poecilia reticulata
EC50 - Crustacea [1]	> 4,4 g/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	154,917 mg/l Test organisms (species): other:green algae
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
LC50 96h fish (1)	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19,3 mg/l Test organisms (species): Daphnia magna

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 - Crustacea [2]	27,8 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	 > 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) 	
NOEC (chronic)	≥ 2,92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
LC50 96h fish (1)	10000 mg/l Test organisms (species): Pimephales promelas	
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas	
Reaction mass of ethyl benzene and xylene		
LC50 96h fish (1)	2,6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 - Crustacea [1]	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia	
NOEC chronic fish	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'	
12.2. Persistence and degradability		
CHALK FINISH		
Persistence and degradability	Not established.	
12.3. Bioaccumulative potential		
CHALK FINISH		
Bioaccumulative potential	Not established.	
12.4. Mobility in soil		
lo additional information available		
12.5. Results of PBT and vPvB assessment		
lo additional information available		
12.6. Other adverse effects		
Additional information	Avoid release to the environment.	
SECTION 13: Disposal considerations		

13.1. Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations Ecology - waste materials

- Dispose of contents/container in accordance with licensed collector's sorting instruction;
 Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA		
ADR	IMDG	ΙΑΤΑ
14.1. UN number		
UN 1950	UN 1950	UN 1950

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	ΙΑΤΑ
14.2. UN proper shippin	g name	
AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document descr	iption	
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard o	lass(es)	
2.1	2.1	2.1
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards	
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary informatio	n available	·
14.6. Special precaution	s for user	
Overland transport		

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading	: CV9, CV12
and handling (ADR)	
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)	
Reference code Applicable on	
3(a)	CHALK FINISH ; Reaction mass of ethyl benzene and xylene ; propan-2-ol; isopropyl alcohol; isopropanol
3(b) CHALK FINISH ; Reaction mass of ethyl benzene and xylene ; propan-2-ol; isopropyl alcohol; isopropanol	
40.	dimethyl ether ; Reaction mass of ethyl benzene and xylene ; propan-2-ol; isopropyl alcohol; isopropanol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

: 69,5 wt%

15.1.2. National regulations

VOC content

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830.

Indication of changes				
Section	Changed item	Change	Comments	
2.1	Adverse physicochemical, human health and environmental effects	Modified		
2.2	Precautionary statements (CLP)	Modified		
4.1	First-aid measures general	Modified		
6.1	Emergency procedures	Modified		
6.2	Environmental precautions	Modified		
6.3	Methods for cleaning up	Modified		
7.1	Hygiene measures	Modified		
7.1	Precautions for safe handling	Modified		
7.2	Storage conditions	Modified		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations a			
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
BLV	Biological limit value		
BOD	Biochemical oxygen demand (BOD)		
COD	Chemical oxygen demand (COD)		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
VOC	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		
ED	Endocrine disrupting properties		

Data sources

 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
 None.

Other information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements				
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4			
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4			
Asp. Tox. 1	Aspiration hazard, Category 1			
Carc. 2	Carcinogenicity, Category 2			
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2			
Flam. Gas 1A	Flammable gases, Category 1A			
Flam. Liq. 2	Flammable liquids, Category 2			
Flam. Liq. 3	Flammable liquids, Category 3			
Press. Gas	Gases under pressure			
Skin Irrit. 2	Skin corrosion/irritation, Category 2			
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation			
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis			
H220	Extremely flammable gas.			
H222	Extremely flammable aerosol.			
H225	Highly flammable liquid and vapour.			
H226	Flammable liquid and vapour.			
H229	Pressurised container: May burst if heated.			
H304	May be fatal if swallowed and enters airways.			
H312	Harmful in contact with skin.			
H315	Causes skin irritation.			
H319	Causes serious eye irritation.			
H332	Harmful if inhaled.			
H335	May cause respiratory irritation.			
H336	May cause drowsiness or dizziness.			
H351	Suspected of causing cancer.			
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.			

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]				
Aerosol 1	H222;H229	Expert judgment		
Eye Irrit. 2	H319	Expert judgment		

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.