

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : TECH INOX HOUSEHOLD E150
Product code : 150
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public
Use of the substance/mixture : Spraying paint (spray can)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Novasol Spray, S.A.
P.I.: Empalme - C/ Empalme, 27
Llorenç del Penedès - Spain
T +34 977 677 305
novasol@novasolspray.com - www.novasolspray.com

1.4. Emergency telephone number

Emergency number : +34 977 677 305
Office hours: Monday-Friday 8:30 AM-6:00 PM GMT+1

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.
Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger
Hazardous ingredients : ethyl acetate; butanone; ethyl methyl ketone
Hazard statements (CLP) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|--------------------------------|--|
| Precautionary statements (CLP) | : P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P271 - Use only outdoors or in a well-ventilated area. P312 - Call doctor if you feel unwell. |
| EUH-statements | : EUH066 - Repeated exposure may cause skin dryness or cracking. EUH208 - Contains nickel powder; [particle diameter < 1mm]. May produce an allergic reaction. |
| Child-resistant fastening | : Not applicable |
| Tactile warning | : Not applicable |

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|--|-------------|--|
| dimethyl ether (Aerosol propellants) substance with a Community workplace exposure limit (Note U) | (CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8 (REACH-no) 01-2119472128-37 | ≥ 50 – < 80 | Flam. Gas 1A, H220 Press. Gas |
| butanone; ethyl methyl ketone | (CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43 | ≥ 20 – < 50 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| (Note C) | | ≥ 7 – < 10 | Flam. Liq. 2, H225 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 |
| ethyl acetate | (CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46 | ≥ 7 – < 10 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| substance with a Community workplace exposure limit | (CAS-No.) 7440-47-3 (EC-No.) 231-157-5 (REACH-no) 01-2119485652-31 | ≥ 0,1 – < 1 | STOT RE 1, H372 Aquatic Chronic 4, H413 |
| nickel powder; [particle diameter < 1mm] | (CAS-No.) 7440-02-0 (EC-No.) 231-111-4 (EC Index-No.) 028-002-01-4 | < 1 | Skin Sens. 1, H317 Carc. 2, H351 STOT RE 1, H372 Aquatic Chronic 3, H412 |
| 2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit | (CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7 (REACH-no) 01-2119475791-29 | < 0,1 | Flam. Liq. 3, H226 |

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : IF exposed or concerned: Get medical advice/attention. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|--|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Eye irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
|------------------------------|--|

5.2. Special hazards arising from the substance or mixture

| | |
|--|---|
| Fire hazard | : Extremely flammable aerosol. |
| Explosion hazard | : Pressurised container: May burst if heated. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Advice for firefighters

| | |
|--------------------------------|--|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
|--------------------------------|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

| | |
|----------------------|--|
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. |
|----------------------|--|

6.1.2. For emergency responders

| | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|---|

6.2. Environmental precautions

Avoid release to the environment.

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| dimethyl ether (115-10-6) | |
|-----------------------------------|---------------------------------|
| EU - Occupational Exposure Limits | |
| Local name | Dimethylether |
| IOELV TWA (mg/m ³) | 1920 mg/m ³ |
| IOELV TWA (ppm) | 1000 ppm |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |

| ethyl acetate (141-78-6) | |
|-----------------------------------|------------------------------------|
| EU - Occupational Exposure Limits | |
| Local name | Ethyl acetate |
| IOELV TWA (mg/m ³) | 734 mg/m ³ |
| IOELV TWA (ppm) | 200 ppm |
| IOELV STEL (mg/m ³) | 1468 mg/m ³ |
| IOELV STEL (ppm) | 400 ppm |
| Regulatory reference | COMMISSION DIRECTIVE (EU) 2017/164 |

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

butanone; ethyl methyl ketone (78-93-3)

EU - Occupational Exposure Limits

| | |
|---------------------------------|---------------------------------|
| Local name | Butanone |
| IOELV TWA (mg/m ³) | 600 mg/m ³ |
| IOELV TWA (ppm) | 200 ppm |
| IOELV STEL (mg/m ³) | 900 mg/m ³ |
| IOELV STEL (ppm) | 300 ppm |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |

EU - Occupational Exposure Limits

| | |
|---------------------------------|---------------------------------|
| Local name | Xylene, mixed isomers, pure |
| IOELV TWA (mg/m ³) | 221 mg/m ³ |
| IOELV TWA (ppm) | 50 ppm |
| IOELV STEL (mg/m ³) | 442 mg/m ³ |
| IOELV STEL (ppm) | 100 ppm |
| Notes | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |

nickel powder; [particle diameter < 1mm] (7440-02-0)

EU - Occupational Exposure Limits

| | |
|--------------------------------|---|
| Local name | Nickel metal |
| IOELV TWA (mg/m ³) | 0,005 mg/m ³ (respirable fraction) |
| Notes | (Year of adoption 2011) |
| Regulatory reference | SCOEL Recommendations |

EU - Biological limit values

| | |
|----------------------|--|
| Local name | Nickel and nickel compounds |
| European - BGV | 3 µg/l Parameter: nickel - Medium: urine |
| Regulatory reference | SCOEL List of recommended health-based BLVs and BGVs |

(7440-47-3)

EU - Occupational Exposure Limits

| | |
|--------------------------------|---------------------------------|
| Local name | Chromium metal |
| IOELV TWA (mg/m ³) | 2 mg/m ³ |
| Regulatory reference | COMMISSION DIRECTIVE 2006/15/EC |

2-methoxy-1-methylethyl acetate (108-65-6)

EU - Occupational Exposure Limits

| | |
|---------------------------------|--------------------------------|
| Local name | 2-Methoxy-1-methylethylacetate |
| IOELV TWA (mg/m ³) | 275 mg/m ³ |
| IOELV TWA (ppm) | 50 ppm |
| IOELV STEL (mg/m ³) | 550 mg/m ³ |

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|----------------------|---------------------------------|
| IOELV STEL (ppm) | 100 ppm |
| Notes | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Butyl rubber gloves (EN 374)

Eye protection:

eye protection (EN166)

Respiratory protection:

If vapour is released : Disposable half mask

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Liquid |
| Colour | : Metallic. |
| Odour | : No data available |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : -25 °C Aerosol jet |
| Flash point | : -41 °C Aerosol jet |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : Pressurised container: May burst if heated. |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

Not volatile : 11,5 wt%

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

VOC content : 88,5 wt%
VOC content : 675 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

dimethyl ether (115-10-6)

| | |
|---------------------------|---|
| LC50 inhalation rat (ppm) | 164000 ppm Animal: rat, Animal sex: male, 95% CL: 142000 - 203000 |
|---------------------------|---|

ethyl acetate (141-78-6)

| | |
|---|-----------------------|
| LD50 oral rat | 4100 mg/kg |
| LD50 dermal rabbit | 20000 mg/kg |
| LD50 dermal | > |
| LC50 inhalation rat (mg/l) | > 44 g/m ³ |
| LC50 inhalation rat (Vapours - mg/l/4h) | 22,5 mg/l/4h |

butanone; ethyl methyl ketone (78-93-3)

| | |
|----------------------------|--------------|
| LD50 oral rat | 4000 mg/kg |
| LD50 dermal rat | mg/kg |
| LD50 dermal rabbit | 6400 mg/kg |
| LC50 inhalation rat (mg/l) | 23,5 mg/l/4h |

nickel powder; [particle diameter < 1mm] (7440-02-0)

| | |
|---------------|--|
| LD50 oral rat | > 9000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
|---------------|--|

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|-----------|--------|
| LD50 oral | > 9000 |
|-----------|--------|

(7440-47-3)

| | |
|----------------------------|--|
| LC50 inhalation rat (mg/l) | > 5,41 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |
|----------------------------|--|

2-methoxy-1-methylethyl acetate (108-65-6)

| | |
|---|------------|
| LD50 oral rat | 8532 mg/kg |
| LD50 oral | > |
| LD50 dermal rat | 5100 |
| LD50 dermal | > |
| LC50 inhalation rat (mg/l) | > 10,8 |
| LC50 inhalation rat (Vapours - mg/l/4h) | 30 mg/l/4h |

| | |
|-----------------------------------|----------------------------------|
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |

| | |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

(7440-47-3)

| | |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

| | |
|------------------------|--------------------------------------|
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause drowsiness or dizziness. |
| STOT-repeated exposure | : Not classified |

(7440-47-3)

| | |
|---|---|
| LOAEC (inhalation, rat,dust/mist/fume, 90 days) | ≥ 0,0044 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) |
|---|---|

| | |
|-------------------|------------------|
| Aspiration hazard | : Not classified |
|-------------------|------------------|

TECH INOX HOUSEHOLD E150

| | |
|-----------|---------|
| Vaporizer | Aerosol |
|-----------|---------|

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|---|
| Ecology - general | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified |

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

dimethyl ether (115-10-6)

| | |
|--------------------|--|
| LC50 96h fish (1) | > 4,1 g/l Test organisms (species): Poecilia reticulata |
| EC50 Daphnia 1 | > 4,4 g/l Test organisms (species): Daphnia magna |
| EC50 96h algae (1) | 154,917 mg/l Test organisms (species): other:green algae |

butanone; ethyl methyl ketone (78-93-3)

| | |
|-------------------|-----------|
| LC50 96h fish (1) | 3220 mg/l |
| EC50 Daphnia 1 | 5091 mg/l |

| | |
|--------------------------------|---|
| EC50 Daphnia 1 | > 3,4 mg/l Test organisms (species): Ceriodaphnia dubia |
| EC50 other aquatic organisms 1 | > 3,4 mg/l |

2-methoxy-1-methylethyl acetate (108-65-6)

| | |
|-------------------|----------|
| LC50 96h fish (1) | 161 mg/l |
| EC50 Daphnia 1 | 481 mg/l |

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate (108-65-6)

| | |
|---|------|
| BCF fish 1 | 1 |
| Partition coefficient n-octanol/water (Log Pow) | 0,43 |

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information




In accordance with ADR / RID / IMDG / IATA / ADN

| ADR | IMDG | IATA |
|--------------------------------------|----------|---------------------|
| 14.1. UN number | | |
| UN 1950 | UN 1950 | UN 1950 |
| 14.2. UN proper shipping name | | |
| AEROSOLS | AEROSOLS | Aerosols, flammable |

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Transport document description | | |
|---|---|---|
| UN 1950 AEROSOLS, 2.1, (D) | UN 1950 AEROSOLS, 2.1 | UN 1950 Aerosols, flammable, 2.1 |
| 14.3. Transport hazard class(es) | | |
| 2.1 | 2.1 | 2.1 |
|  |  |  |
| 14.4. Packing group | | |
| Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | |
| Dangerous for the environment : No | Dangerous for the environment : No Marine pollutant : No | Dangerous for the environment : No |
| No supplementary information available | | |

14.6. Special precautions for user

Overland transport

| | |
|---|----------------------|
| Classification code (ADR) | : 5F |
| Special provisions (ADR) | : 190, 327, 344, 625 |
| Limited quantities (ADR) | : 1I |
| Excepted quantities (ADR) | : E0 |
| Packing instructions (ADR) | : P207 |
| Special packing provisions (ADR) | : PP87, RR6, L2 |
| Mixed packing provisions (ADR) | : MP9 |
| Transport category (ADR) | : 2 |
| Special provisions for carriage - Packages (ADR) | : V14 |
| Special provisions for carriage - Loading, unloading and handling (ADR) | : CV9, CV12 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Tunnel restriction code (ADR) | : D |

Transport by sea

| | |
|-----------------------------------|------------------------------------|
| Special provisions (IMDG) | : 63, 190, 277, 327, 344, 381, 959 |
| Packing instructions (IMDG) | : P207, LP200 |
| Special packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D |
| EmS-No. (Spillage) | : S-U |
| Stowage category (IMDG) | : None |
| Stowage and handling (IMDG) | : SW1, SW22 |
| Segregation (IMDG) | : SG69 |

Air transport

| | |
|--|--------------------|
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 88,5 wt%

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830.

| Section | Changed item | Change | Comments |
|---------|---|----------|----------|
| | Classification code (RID) | Added | |
| 2.1 | Adverse physicochemical, human health and environmental effects | Modified | |
| 2.2 | Precautionary statements (CLP) | Modified | |
| 4.1 | First-aid measures after skin contact | Modified | |
| 4.1 | First-aid measures general | Modified | |
| 4.2 | Symptoms/effects after skin contact | Modified | |
| 6.1 | Emergency procedures | Modified | |
| 6.3 | Methods for cleaning up | Modified | |
| 7.1 | Hygiene measures | Modified | |
| 7.1 | Precautions for safe handling | Modified | |
| 9.1 | Colour | Modified | |

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

| | |
|--------------|-----------|
| Aerosol 1 | H222;H229 |
| Eye Irrit. 2 | H319 |
| STOT SE 3 | H336 |

Full text of H- and EUH-statements:

| | |
|-------------------------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |

TECH INOX HOUSEHOLD E150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|-------------------|--|
| Aquatic Chronic 3 | Hazardous to the aquatic environment — Chronic Hazard, Category 3 |
| Aquatic Chronic 4 | Hazardous to the aquatic environment — Chronic Hazard, Category 4 |
| Carc. 2 | Carcinogenicity, Category 2 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Gas 1A | Flammable gases, Category 1A |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Press. Gas | Gases under pressure |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| Skin Sens. 1 | Skin sensitisation, Category 1 |
| STOT RE 1 | Specific target organ toxicity — Repeated exposure, Category 1 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H229 | Pressurised container: May burst if heated. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects. |
| H413 | May cause long lasting harmful effects to aquatic life. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| EUH208 | Contains nickel powder; [particle diameter < 1mm]. May produce an allergic reaction. |

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

| | | |
|--------------|-----------|-----------------------|
| Aerosol 1 | H222;H229 | On basis of test data |
| Eye Irrit. 2 | H319 | Calculation method |
| STOT SE 3 | H336 | Calculation method |

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.