



Wood Stripper

GENERAL DESCRIPTION

Our best stain stripper removes all oil and latex deck coatings and removes mold and mildew stains from wood surfaces. Use to strip old finishes and stains from exterior wood, reduce mill glaze or eliminate grade stamps on wood.

RECOMMENDED USES

For exterior use only. Use on decks, wood siding, shake and shingle siding, fences, outdoor furniture, and other wood surfaces. Use on previously coated wood surfaces that need to be stripped.

PRODUCT INFORMATION

FLD138XI

PACKAGING

1 - Gallon (3.78 L)

FEATURES / BENEFITS

Ready to use

Removes oil-based and water-based coatings

Brush on, let sit for 5 to 45 minutes and rinse with light scrubbing

PRODUCT DATA

PRODUCT TYPE: Sodium Hydroxide Solution

WEIGHT/GALLON: 9.2 lbs. (4.2 kg) +/- 0.2 lbs. (91 g)

COVERAGE: Approximately 50 to 150 sq. ft. (4.5 to 14 sq. meters) per U.S. gallon (3.78 L). Coverage figures may vary depending on texture of the wood and application method.

RECOMMENDED SPRAY EQUIPMENT: Use a plastic, pump-style garden sprayer and hose.

CLEANUP: Clean tools with warm, soapy water immediately after use.

STORAGE: Store in a cool, dry location, in a tightly closed, plastic container. Do not reuse container. Rinse container thoroughly before disposal.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

Wood Stripper

DIRECTIONS FOR USE

AREA PREPARATION: Spray all plants and vegetation liberally with water before and after application. Cover delicate vegetation to avoid damage. Do not allow to come in contact with metal, fabric, floor coverings, or lawn furniture.

SAFETY PRECAUTIONS: Wear chemical resistant gloves, safety goggles and protective clothing. Surfaces are slippery when wet. Use caution when walking on wet surfaces during application. Product may damage metal components of spray equipment. Avoid contact with aluminum and tin metals.

APPLICATION: Apply when air, surface, and product temperatures are between 50°F (10°C) and 90°F (32°C). Thoroughly shake or stir prior to use. DO NOT THIN. Use product full strength. Apply liberally with a nylon brush or roller. Wait 5 to 45 minutes for stain stripper to soften or dissolve coating. Coating will easily rinse off when ready. Scrub areas where needed with a stiff bristle brush. Work in the direction of the wood grain to minimize grain raising. Rinse wood thoroughly with water from a garden hose or power washer at a setting of 500 to 1200 psi to eliminate scrubbing. Do not allow stain stripper to dry. If drying occurs, mist with water and reapply. Do not allow stain stripper to come into contact with bare metal or surfaces that are to remain coated. Stain stripper may cause darkening on tannin-rich woods, such as mahogany, cedar, redwood, etc. Wood brightener is recommended to remove this darkening from the wood. Test a small, inconspicuous area prior to use to ensure acceptable appearance

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

LIMITATIONS OF USE

PROTECT FROM FREEZING. KEEP IN AN UPRIGHT POSITION.

PRECAUTIONS

DANGER! CAUSES SEVERE EYE AND SKIN BURNS. HARMFUL IF INHALED. HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL IF SWALLOWED. CAUSES RESPIRATORY TRACT IRRITATION. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness, and nausea and may lead to unconsciousness. The product may not be stable under certain conditions of storage or use: high temperature/ pressure hazard. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray, or mist arising from the application of this preparation. Use personal protective equipment as required. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. Call physician immediately. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515.

© 2021 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Flood and the Flood and Paintbrush Design are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.flood.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec) J4B 7L4

T.D. FLD138XI 4-2021
(Supersedes 1/2016)