

UGL® 50-Year Lasticaulk® Acrylic Latex Caulk with Silicone

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

UGL 50-Year Lasticaulk is a non-staining, paintable acrylic latex-silicone compound designed for superior adhesion and longer life. Lasticaulk guns easily and forms a durable, elastic, watertight seal that resists weather and mildew. Lasticaulk helps protect your home against drafts and moisture. Will not affect painted surfaces.

- Forms a durable, elastic, water-tight seal
- Resists water, weather and mildew
- Bonds perfectly to wood, masonry, metal, tile or glass
- Protects homes against drafts and moisture
- Warranted for 50 years
- Paintable immediately

BASIC USES

The product can be used on interior or exterior surfaces such as around windows, doors, siding, sills, thresholds, eaves, soffits, gutters, downspouts, flashings, air conditioners, vents, porches, decks, countertops and gas pipe and plumbing entrances and exits. It bonds perfectly to wood, masonry, metal, tile or glass.

LIMITATIONS

Not for use as an expansion joint sealant. Not recommended for marine use or on areas below water level or grade level.

TECHNICAL DATA

COMPOSITION:

Acrylic latex - silicone

SHEEN:

N/A

% WEIGHT SOLIDS:

White: 80%
Almond: 80%
Gray: 80%

Brown: 80%
Clear: 60%

% VOLUME SOLIDS:

White: 69%
Almond: 69%
Gray: 69%
Brown: 69%
Clear: 58%

DENSITY (LBS./US GAL.):

White, Almond, Gray, Brown: 12.7-13.0
Clear: 8.6

VISCOSITY:

N/A

pH:

White, Almond, Gray, Brown: 7.8
Clear 9.0

COLORS:

- 4 Colors & Clear

CURE TIME:

- 12 Hours

Note: Maximum cure and dry time will be prolonged when slightly humid or when damp, cool conditions prevail.

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE:

- 36 Linear ft. per 1/4" bead

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

3 Years- unopened container

FREEZE/THAW:

CONTAINER SIZES:

Ten and one-half fluid ounces (US)
caulk tube

VOC

White, Almond, Gray, Brown: 55-57 g/L
Clear: 32 g/L

TINTING

N/A

SURFACE PREPARATION

Opening to be sealed (up to ½-inch by ¼-inch wide) must be free from moisture, mildew, frost, dirt, rust and loose caulk, putty or mortar. Deep cracks (over ¼-inch) should be filled to within ¼-inch of surface with a backing material such as oakum prior to caulking. Place cartridge in any standard caulk gun.

Select size of bead by cutting plastic spout at number indicated (5/16, 1/4 or 1/8 inch) on the cartridge's tip. Cut spout at 45-degree angle.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start,



CURE TIME:
12 Hours



CLEAN-UP:
Soap and Water



COVERAGE:
1 Application



SPREAD RATE:
36 Linear Feet/
1/4 Inch Bead

find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Angle spout tip over space to be filled. Start at bottom of crack and work up as void is filled. The caulk bead may be easily smoothed with wet finger or cloth. Before curing, remove excess caulk with damp cloth.

Lasticaulk can be painted over immediately with latex paint. Allow compound to dry overnight before applying an oil based paint.

The drying and curing of all latex caulks (normally cured in 12 hours) is affected by temperatures and humidity. Apply only when air and surface temperatures are above 50°F (10°C). Application under conditions of extreme dampness or high humidity prolongs drying and curing time by as much as 36 hours, rendering caulk vulnerable to driving rain.

VENTILATION

N/A

CAUTION

DO NOT TAKE INTERNALLY. KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulators.

FIRST AID

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected area with soap and water. Consult a physician if irritation persists.

INGESTION: Drink 1 or 2 glasses of water. If individual is drowsy or unconscious do not give anything by mouth. Consult a physician, medical facility or poison control center for

advise about whether to induce vomiting.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

WARRANTY

Use contents of cartridge as directed within one year from date of purchase. This warranty applies to residential use only.

LIMITED WARRANTY

United Gilsonite Laboratories ("UGL") warrants, subject to the limitations set forth herein, that this product, under normal use and proper storage, will be free from defects in material or workmanship and merchantable for a period of fifty (50) years from the original date of purchase. This limited warranty extends to the original consumer purchaser of the product only and is non-transferable. If this product is found to be defective by UGL within the warranty period, you will receive a replacement of the product or, at UGL's option, a full refund of the purchase price upon presentation of proof of purchase (original sales receipt). This limited warranty excludes failure to apply the product to a properly prepared bare surface in accordance with UGL's instructions provided with this product. UGL MAKES NO FURTHER EXPRESS WARRANTIES. THIS LIMITED WARRANTY EXCLUDES (1) LABOR AND ALL OTHER COSTS ASSOCIATED WITH THE APPLICATION OR REMOVAL OF THE PRODUCT OR ANY REPLACEMENT PRODUCT, AND (2) ANY INDIRECT, SPECIAL, EXEMPLARY, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the limitation or exclusion of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This limited warranty gives you specific legal rights and you may also have other legal rights which vary from state to state. To make a warranty claim please contact (with proof of purchase) the store where you purchased the product or contact UGL directly at 1-800-848-7253 (Consumer Hotline) or by mail at UGL Consumer Inquiry Department, P.O. Box 70, Scranton PA 18501-0070.

SPECIFICATION

ASTM Specification C-834-76

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.



50-Year Lasticaulk®
10.5 FL. OZ. CARTRIDGE

10/Case



White
33307



Clear
33407



Almond
33607



Brown
33707



Gray
33807

NOTE: COLOR SWATCHES ARE REPRESENTATIONAL ONLY.

LR813