

UGL® Tub & Tile Caulk

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

UGL Latex Tub and Tile Caulk is a nonstaining, silicone-fortified sealant. This mildew-resistant compound stays white and provides excellent adhesion to most building materials. Tub and Tile Caulk goes on easily and forms a water tight seal. It bonds to metal, wood, masonry, tile or glass.

- Waterproof around tubs, sinks and showers
- Mildew resistant, non-staining
- Excellent adhesion to most building materials

BASIC USES

Tub and Tile Caulk can be used on a variety of interior and exterior surfaces including window and door frames, sinks, tubs and showers.

LIMITATIONS

N/A

TECHNICAL DATA

COMPOSITION:

Acrylic fortified with silicone

SHEEN:

% WEIGHT SOLIDS:

84%

% VOLUME SOLIDS:

74%

DENSITY (LBS./US GAL.):

13.6 lbs./gallon

VISCOSITY:

N/A

pH:

N/A

COLORS:

- White

CURE TIME:

- 48-72 Hours

Note: Maximum cure and dry time will be prolonged when slightly humid or when damp, cool conditions prevail.

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US GAL.):

- 36 Linear ft. per 1/4" bead

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

3 Years-unopened

FREEZE/THAW:

Protect from freezing

CONTAINER SIZES:

Six fluid ounce (US) squeeze tube

VOC

14 g/L

TINTING

N/A

SURFACE PREPARATION

Opening to be sealed must be dry and free of moisture, dirt, grease, dust, soap film and loose caulk.

Rubbing alcohol is recommended to remove soap film.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Apply only when air and surface temperatures are above 50° F (10° C). Place spout-tip at an angle over area to be sealed. If area is deeper than 1/4-inch fill space with oakum or backing material up to 1/4-inch deep. Start at the bottom of the area to be sealed and work up as the void is filled. Wipe off excess caulk with a damp cloth before it dries (approximately 30 minutes).

Note: Knead tube in hand before applying.

Allow Tub & Tile Caulk to dry 48-72 hours before using shower. Temperature and/or high humidity will extend drying time.

After caulk is applied, wait one hour before painting with a latex paint. Wait overnight before painting with an oil based paint.

To reset tile, apply liberally at center and each corner. Place tile firmly in proper position. Clean tools with soap and water upon completion.

VENTILATION



CURE TIME:

48-72 Hours



CLEAN-UP:

Soap and Water



COVERAGE:

1 Application



SPREAD RATE:

36 Linear Feet/
1/4 Inch Bead

N/A

CAUTION

DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulators.

FIRST AID

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected area with soap and water. Consult a physician if irritation persists.

INGESTION: Drink 1 or 2 glasses of water. If individual is drowsy or unconscious do not give anything by mouth. Consult a physician, medical facility or poison control center for advise about whether to induce vomiting.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

WARRANTY

N/A

SPECIFICATION

N/A



Tub & Tile Caulk
6 FL. OZ. TUBE



White

12/Case30705

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

NOTE: COLOR SWATCHES ARE REPRESENTATIONAL ONLY.

LR813