



E.S.P.

EASY SURFACE PREP

Product description

E.S.P. is an easy wipe-on/wipe-off product that prepares and primes all-in-one, negating the need for the laborious job of sanding. E.S.P. leaves a bonding film that promotes strong adhesion of new paint to any non-porous surface.

Properties

- Easy wipe-on/wipe-off application.
- Prepares smooth slick surfaces for painting or varnishing.
- May be overpainted with any oil-based or water-based paint or varnish.
- Eliminates time-consuming, laborious sanding.
- May be painted over anytime after 2 hours or up to 7 days later.
- Easy to use.
- Does not soften, remove or dull the old finish.

Basic uses

- For interior and exterior use.
- Lacquers, baked enamels, varnishes, paint: walls, furniture, radiators...
- Ceramics: bathroom.
- Melamine: kitchen furniture.
- Glass.

Technical data

Finish: Clear

Vehicle type: Acrylic/Alkyd resins

Solvent type: Water

Specific gravity: 1.003 ±0.01

Physical state: Liquid

Flammability: Not classed as flammable

Flash point: N/A

Shelf life: 1-year minimum in original unopened packaging

Container size: 1L

Colour: Milky

Drying time: 2 hours, depending on temperature and humidity

VOC: UE limit value for this product (cat. A/h) 30 g/L. (2010). This product contains max. 29 g/L.

Application tools

- Lint free cloth, brush, roller.

Good application practice

- Ensure new finish is compatible with the old finish.
- Remove any loose and flaking old finish.
- For greasy, waxed or varnished surfaces, scrub surface with a green scourer or 00 steel wool soaked with E.S.P. Wipe off all E.S.P. after 5-10 minutes then follow application instructions below.
- Use clean clothes and change them regularly.
- Do not contaminate new clean E.S.P. with old used E.S.P.
- Do not use E.S.P. for dipping.
- Apply between 5°C and 35°C.

Application

- Apply E.S.P. liberally with a clean, dry, lint free cloth. If E.S.P. «crawls» or separates, the surface is not clean. Wipe off E.S.P. and reclean according to above directions.
- Leave to stand 5 minutes then lightly wipe over the surface in one direction with a clean cloth to remove excess E.S.P.
- Allow E.S.P. to dry for 2 hours before applying the finish.

Coverage

- 18 m² per litre.
- Actual coverage will vary depending upon the type, age and texture of the surface.

Restrictions

- Do not overcoat with 2 pack finishes, cellulose, xylene and urethane coatings.

Clean-up

- Soap and water.

Storage

- Keep from freezing.

Safety

- **MSDS available at www.owatrol.com**

