

OWATROL®

SEASONITE®

PROTECTION FOR NEW WOOD

USAGE

- New exterior wood, during the first 12 months of weathering.
- Ideal for soft wood (pine, épicéa, red cedar...) and especially for pressure-treated wood.
- Use on new garden decks, cladding, fences, shakes, shingles and unfinished outdoor furniture.
- Horizontal and vertical surfaces.
- For weathered wood use NET-TROL® and TEXTROL®.

PROPERTIES

- New wood has mill glaze which prevents proper penetration of finishes. SEASONITE® bonds with the top layers of the wood fibres which enables it to control the movement of moisture in and out of the wood.



AVOID THIS!!!



- Dramatically minimises the potential for the wood to split, warp, crack etc during the first year when it is most vulnerable.
- Stabilises and protects against sun and moisture.
- Lets the pores of the wood open naturally.

APPLICATION

- Shake container well before use.
- SEASONITE® should be applied as soon as possible after installing the new outdoor wood structure.
- Wood should be clean and dry or damp but not wet.
- Apply one generous coat to all wood surfaces.
- Soak into the end grain.
- When treating a deck, work SEASONITE® into cracks between boards.
- If dipping shakes or shingles, soak for 10 minutes then allow the excess to drain.
- Do not apply if cold or wet weather is expected within 24 hours.

COVERAGE RATE	APPLICATION TOOLS	TEMPERATURE FOR APPLICATION	DRYING TIME	CLEAN UP SOAP + WATER
5 to 7 m ² /l		+35°C +5°C	12 hours	



EXTERIOR

Owatrol International SL

C/Aragón 179, 5º - 08011 Barcelona - Spain
Tel: +34 934 51 66 04 - Fax: +34 934 52 14 54
info@owatrol.com - www.owatrol.com