

OWATROL®

OWATROL OIL®

PAINT ADDITIVE

USAGE

- Interior / Exterior.
- Additive for oil based paint, air drying alkyds, lacquers and varnishes, one component urethanes and asphalt / petroleum based paint.
- Use on all surfaces (metal, wood, aluminium, plastic, glass, stone etc.)

PROPERTIES

- Improves paint adhesion.
- Prevents paint from cracking and peeling.
- Improves flow of paint and helps eliminate brush or roller marks.
- Improves uniformity and coverage of coat, up to 25% more.
- Keeps wet edge open longer. Ideal for special effects etc.
- Makes the paint rust-inhibiting.
- Colourless – keeps the original appearance.
- Does not “thin” paint, actually adds solid content, does not evaporate.
- Makes paint brushable in warm and cold conditions.

Additive Opportunity

		10°C	20°C	30°C
		Temperature 		
Humidity 	75%	Opportunity	Opportunity	Opportunity
	50%	Opportunity	Sweet Spot for Painting	Opportunity
	25%	Opportunity	Opportunity	Opportunity



Paint with OWATROL OIL®

Paint without OWATROL OIL®

APPLICATION

- Apply the paint.
- To make paint rust-inhibiting, mix 25% OWATROL OIL®, 75% paint.
- To adhere to difficult surfaces, mix 50% OWATROL OIL®, 50% paint.
- To improve paint flow, mix 5-10% OWATROL OIL® with paint.
- Always test for compatibility.

COVERAGE

18 m²/l

APPLICATION
TOOLS



TEMPERATURE
FOR APPLICATION

+35°C
+5°C

DRYING TIME
12 hours

RECOATING
TIME
12-24 hours

CLEAN UP
WHITE-SPIRIT



INTERIOR
EXTERIOR

Owatrol International SL

C/Aragón 179, 5º - 08011 Barcelona - Spain
Tel: +34 934 51 66 04 - Fax: +34 934 52 14 54
info@owatrol.com - www.owatrol.com