

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : OWATROL DECAPANT DSP 800 Product code : owadsp800

1.2. Relevant identified uses of the substance or mixture and uses advised against Stripper gel

## 1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU SA. Address : 29 rue de Wedel, BP 20059, ZI.59541 .CAUDRY.FRANCE. Telephone : +33 (0)3-27-76-60-60. Fax : +33 (0)3-61-54-00-21. accueil@durieu.com

http://www.oxi-peintures.fr

## 1.4. Emergency telephone number : +33 (0)3-45-42-59-59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

### Other emergency numbers

www.centre-antipoison.net

#### **SECTION 2 : HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

### In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Repeated exposure may cause skin dryness or cracking (EUH066).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

### 2.2. Label elements

Signal Word :

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02

DANGER	
Product identifiers :	
606-001-00-8	ACETONE
Hazard statements :	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements - G	eneral :
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statements - Precautionary stateme	revention :

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - R	Response :
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Precautionary statements - D	Disposal :
P501	Dispose of contents/container to

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## **SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

Identification	(EC) 1272/2008	Note	%
NDEX: 606-001-00-8	GHS02, GHS07	[1]	50 <= x % < 100
CAS: 67-64-1	Dgr		
EC: 200-662-2	Flam. Liq. 2, H225		
REACH: 01-2119471330-49	Eye Irrit. 2, H319		
	STOT SE 3, H336		
ACETONE	EUH:066		
INDEX: 603-057-00-5	GHS07		10 <= x % < 25
CAS: 100-51-6	Wng		
EC: 202-859-9	Acute Tox. 4, H332		
REACH: 01-2119492630-38	Acute Tox. 4, H302		
BENZYL ALCOHOL			
NDEX: 298	GHS09, GHS07, GHS08		2.5 <= x % < 10
EC: 918-811-1	Dgr		
REACH: 01-2119463583-34	Asp. Tox. 1, H304 STOT SE 3, H336		
HYDROCARBONS, C10, AROMATICS,	Aquatic Chronic 2, H411		
<1% NAPHTALENE	EUH:066		
INDEX: 607-001-00-0	GHS05	В	1 <= x % < 2.5
CAS: 64-18-6	Dgr	[1]	
EC: 200-579-1	Skin Corr. 1A, H314		
REACH: 01-2119491174-37			
FORMIC ACID			

#### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

### **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

## 4.1. Description of first aid measures

### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

### SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL DECAPANT DSP 800 - owadsp800

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open. If there is any redness, pain or visual impairment, consult an ophthalmologist.

## In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

## In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

## 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

### **SECTION 5 : FIREFIGHTING MEASURES**

## Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

## Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

## Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

## 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

## For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

## 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

## **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

#### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

#### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

## Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

### Packaging

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

### SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Occupational exposure limits :

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
67-64-1	1210	500	-	-	-
64-18-6	9	5	-	-	-

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
67-64-1	500 ppm	750 ppm	-	-	-	
64-18-6	5 ppm	10 ppm	-	-	-	
- German	y - AGW (BAuA - TRG	S 900, 21/06/2010) :	1			
CAS	VME :	VME :	Excess	Notes		
67-64-1	500 ml/m3	1200 mg/m3	2(I)	DFG		
64-18-6	5 ml/m3	9,5 mg/m3	2(I)	DFG, EU, Y		
- France (	(INRS - ED984 :2008)					
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No
67-64-1	500	1210	1000	2420	-	84
64-18-6	5	9	-	-	-	-
- UK / WE	EL (Workplace exposur	e limits, EH40/2005, 20	007):			
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
67-64-1	500 ppm	1500 ppm	-	-	-	
64-18-6	5 ppm	-	-	-	-	
04-10-0	e ppin					

#### 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

### Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

### Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

### **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

### General information :

Physical state :

Fluid liquid.

### Important health, safety and environmental information

pH :	Not relevant.
Boiling point/boiling range :	> 35°C
Flash Point :	-18.00 °C.
Vapour pressure (50°C) :	Not relevant.
Density :	< 1
Water solubility :	Insoluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.

## 9.2. Other information

No data available.

## **SECTION 10 : STABILITY AND REACTIVITY**

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

- Avoid :
- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

### **SECTION 11 : TOXICOLOGICAL INFORMATION**

#### 11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

# 11.1.1. Substances

#### Acute toxicity :

HYDROCARBONS, C10, AROMATICS, <1%	% NAPHTALENE
Oral route :	LD50 > 5000 mg/kg
	Species : Rat
	OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)
Dermal route :	LD50 > 2000 mg/kg
	Species : Rabbit
	OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)
Inhalation route :	LC50 = 4.688 mg/l
	Species : Rat

	WATROL DECAPANT DSP 800 - owadsp800		
		OCDE Ligne directrice 403 (Toxicité aiguë	par inhalation)
	Germ cell mutagenicity :		
	HYDROCARBONS, C10, AROMATICS, <1% NAPHTA	LENE	
		No mutagenic effect.	
	Carcinogenicity :		
	HYDROCARBONS, C10, AROMATICS, <1% NAPHTA	IENE	
	Carcinogenicity Test :	Negative.	
		No carcinogenic effect.	
	Reproductive toxicant :		
	HYDROCARBONS, C10, AROMATICS, <1% NAPHTA	LENE	
	No toxic effect for reproduction		
		OCDE Ligne directrice 414 (Étude de la tox prénatal)	icité pour le développement
	11.1.2. Mixture		
	No toxicological data available for the mixture.		
s	ECTION 12 : ECOLOGICAL INFORMATION		
	Harmful to aquatic life with long lasting effects.		
	The product must not be allowed to run into drains or wa	iterways.	
	12.1. Toxicity	2	
	12.1.1. Substances		
	HYDROCARBONS, C10, AROMATICS, <1% NAPHTA		
	Fish toxicity :	Species : Perca fluviatilis	
	Crustacean toxicity :	EC50 <= 10 mg/l	
		Species : Daphnia magna	
		Duration of exposure : 48 h	
	Algae toxicity :	ECr50 = 11 mg/l	
	<u></u>	Species : Pseudokirchnerella subcapitata	
		Duration of exposure : 72 h	
	12.1.2. Mixtures		
	No aquatic toxicity data available for the mixture.		
	12.2. Persistence and degradability		
	12.2.1. Substances		
	HYDROCARBONS, C10, AROMATICS, <1% NAPHTA	LENE	
	HYDROCARBONS, C10, AROMATICS, <1% NAPHTA Biodegradability :	LENE no degradability data is available, the subst degrading quickly.	ance is considered as not
		no degradability data is available, the subst	ance is considered as not
	Biodegradability :	no degradability data is available, the subst	ance is considered as not
	Biodegradability : 12.3. Bioaccumulative potential	no degradability data is available, the subst	ance is considered as not
	Biodegradability : <b>12.3. Bioaccumulative potential</b> No data available.	no degradability data is available, the subst	ance is considered as not
	Biodegradability : <b>12.3. Bioaccumulative potential</b> No data available. <b>12.4. Mobility in soil</b>	no degradability data is available, the subst	ance is considered as not
	Biodegradability : <b>12.3. Bioaccumulative potential</b> No data available. <b>12.4. Mobility in soil</b> No data available.	no degradability data is available, the subst	ance is considered as not
	Biodegradability : <b>12.3. Bioaccumulative potential</b> No data available. <b>12.4. Mobility in soil</b> No data available. <b>12.5. Results of PBT and vPvB assessment</b>	no degradability data is available, the subst	ance is considered as not

Version 8.1 (01-09-2015) - Page 7/9

# SECTION 13 : DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

# 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

## **SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

#### 14.1. UN number

1993

#### 14.2. UN proper shipping name

UN1993=FLAMMABLE LIQUID, N.O.S. (acetone)

#### 14.3. Transport hazard class(es)

- Classification :



14.4. Packing group

... II

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	П	3	33	1 L	274 601	E2	2	D/E
							640D			
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	3	-	II	1 L	F-E,S-E	274	E2			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	II	353	5 L	364	60 L	A3	E2	
	3	-	II	Y341	1 L	-	-	A3	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

## **SECTION 15 : REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

## - Container information:

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :
  - No data available.
- 15.2. Chemical safety assessment

No data available.

## **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.				
H302	Harmful if swallowed.				
H304	May be fatal if swallowed and enters airways.				
H314	Causes severe skin burns and eye damage.				
H319	Causes serious eye irritation.				
H332	Harmful if inhaled.				
H336	May cause drowsiness or dizziness.				
H411	Toxic to aquatic life with long lasting effects.				
EUH066	Repeated exposure may cause skin dryness or cracking.				

## Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.