

## UGL® NUDECK® ROOF CEMENT

## MANUFACTURER

## UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



(US) caulk tube

## PRODUCT DESCRIPTION

NUDECK Roof Cement is a latex base construction-grade elastomeric caulking sealant designed for cementing and waterproofing chimney and dormer flashings, valley joints and all types of roof seams. NUDECK may be used on WET OR DRY surfaces and retains its elasticity and water resistance for years. The elastomeric and adhesive properties of NUDECK produce a tough and flexible sealant designed to resist variations in temperature and weather. VOC compliant and odor free.

- Forms a durable, elastic, water-tight seal
- Resists water, weather and mildew
- Bonds perfectly to wood, masonry, metal, tile or glass
- Protects homes against drafts and moisture
- Warranted for 50 years
- Paintable immediately

## BASIC USES

NUDECK is ideal sealant for most roofing and waterproofing projects. NUDECK ROOF CEMENT is ideal for sealing leaks in and around asphalt built-up-roofs, shingles, joints, chimney cracks, skylights, vents, downspouts, gutters and leaks on slate or metal roofs. NUDECK may also be used to improve wind resistance on low slope shingle roofs.

## LIMITATIONS

Do not use indoors or when rain is imminent.

## TECHNICAL DATA

## COMPOSITION:

Latex - elastomeric

## SHEEN:

N/A

## % WEIGHT SOLIDS:

50%

## % VOLUME SOLIDS:

47%

## DENSITY (LBS./US GAL.):

8.6

## VISCOSITY:

N/A

## pH:

6.3

## COLORS:

- Black

## CURE TIME:

- 12 Hours

**Note:** Maximum cure and dry time will be prolonged when slightly humid or when damp, cool conditions prevail.

## CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## COVERAGE:

- 25 Linear ft. per 1/4" bead

**Note:** Actual coverage will vary depending upon application method, surface texture and porosity.

## RECOMMENDED FILM THICKNESS/COAT:

N/A

## FLASH POINT:

N/A

## SHELF LIFE:

3 Years-unopened container

## FREEZE/THAW:

Protect from freezing

## CONTAINER SIZES:

Ten and one-hundredth fluid ounce

## VOC

Does not exceed 25% g/L

## TINTING

N/A

## SURFACE PREPARATION

All surfaces to be caulked should be clean and free from oil, grease, rust, dirt, mud, slag, paint and loose particles (such as stones, gravel or pebbles) before applying NUDECK.

## WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## APPLICATION

May be applied to wet or dry surfaces when air and surface temperatures are above 50°F (10°C). If applied to a wet surface all puddles of water must be removed. NUDECK normally cures in 12 hours. Application under conditions of extreme dampness or high humidity prolongs drying, rendering sealant vulnerable to driving rain. Cut end of plastic spout at 45° angle to desired bead size. NUDECK should be applied directly over the



**CURE TIME:**  
12 Hours



**CLEAN-UP:**  
Soap and Water



**COVERAGE:**  
1 Application



**SPREAD RATE:**  
25 Linear Feet/  
1/4 Inch Bead

crack using a standard open cradle caulking gun. Use a trowel to smooth the caulk onto the surface. An application rate of 1/4" x 1/4" bead of caulk will yield approximately 25 linear feet per 10.1 oz. caulking cartridge. Coverage rate may vary depending on desired thickness and surface to be caulked. NUDECK must be dry before exposure to water.

## VENTILATION

N/A

## CAUTION

Avoid prolonged contact with skin. Close container after each use.

KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulators.

## FIRST AID

**EYES:** Flush immediately with large amounts of water for at least 15 minutes. Seek medical attention.

**SKIN:** Wash affected area with soap and water. Consult a physician if irritation persists.

**INGESTION:** Do not induce vomiting. Seek medical attention.

**INHALATION:** Remove to fresh air. If discomfort continues, administer oxygen and get medical attention

For additional health and safety information please refer to the "Materials Safety Data Sheet".

## WARRANTY

N/A

## SPECIFICATION

N/A



Nudeck® Roof Cement  
10.1 FL. OZ. CARTRIDGE 10/Case .....31910



Black

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

**NOTE:** COLOR SWATCHES ARE REPRESENTATIONAL ONLY.

**LR813**