



Wood Stripper

GENERAL DESCRIPTION

Our best stain stripper removes all oil and latex deck coatings, mold, mildew and stains from wood surfaces. May be used full strength or can be diluted for multiple uses. Use to strip old finishes and stains from exterior wood, reduce mill glaze or eliminate grade stamps on wood.

RECOMMENDED USES

For exterior use only. Use on decks, wood siding, shakes, shingles, and fences. Use on previously coated wood surfaces that need to be stripped.

PRODUCT INFORMATION

FLD138

PACKAGING

1 - Gallon (3.78 L)

PRODUCT DATA

PRODUCT TYPE: Sodium Hydroxide Solution

WEIGHT/GALLON: 8.9 lbs. (4.1 kg) +/- 0.2 lbs. (91 g)

COVERAGE: One gallon (3.78 liters) will clean approximately 100-125 sq. ft. (9.3-11.6 sq. meters). Coverage will vary depending on type, age and texture of wood.

RECOMMENDED SPRAY EQUIPMENT: Use a plastic, pump-style garden sprayer and hose.

CLEANUP: Rinse tools and spray equipment thoroughly with water.

STORAGE: Store in a cool dry location in tightly closed plastic container. Avoid exposure to sunlight. Do not reuse container. Rinse container thoroughly before disposal.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

FEATURES

Ready to use

Removes oil-based and water-based coatings

Brush on, let sit for 30 minutes and rinse with light scrubbing

Wood Stripper

DIRECTIONS FOR INTERIOR AND EXTERIOR USE

AREA PREPARATION: Spray all plants and vegetation liberally with water before and after application. Cover delicate vegetation to avoid damage. Do not allow to come in contact with metal, fabric, floor coverings, or lawn furniture.

SAFETY PRECAUTIONS: Wear chemical resistant gloves, safety goggles and protective clothing. Surfaces are slippery when wet. Use caution when walking on wet surfaces during application. Product may damage metal components of spray equipment. Avoid contact with aluminum and tin metals.

MIXING DIRECTIONS: To strip finishes and stains and remove grade stamps, use full strength. To reduce mill glaze, remove natural wood chemicals, or to remove factory-applied sealers, add one quart (946 mL) **FLOOD Wood Stripper** per gallon (3.78 liters) of water. If mildew stains are present, treat in one step by adding one quart (946 mL) of bleach to one gallon (3.78 liters) of **FLOOD Wood Stripper**.

APPLICATION: Shake well or stir thoroughly before using. Do not apply on a hot surface; product will dry too rapidly. For vertical surfaces, work from bottom to top to avoid streaking. Apply product evenly with a brush, roller or garden sprayer to an area you can work in 20–30 minutes. Allow product to stand wet on the surface for 20–30 minutes. Make sure to keep surface wet, rewet with **FLOOD Wood Stripper** if necessary. When finish begins to lift from surface, scrub with a stiff synthetic bristle brush (do not use a wire brush). Rinse surface and adjacent areas using highest pressure from a hose, or pressure wash at 500 psi with a 25° nozzle held 12–15 inches from the surface. If stubborn areas remain, repeat application in those areas. Allow wood to dry for 48 hours before staining or painting. **FLOOD Wood Stripper** may darken Cedar or Redwood. To brighten after using product, use **FLOOD All-Purpose Deck Wash** and spray or roll onto the surface. Wait 10–15 minutes then rinse off with fresh water.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITATIONS OF USE

PROTECT FROM FREEZING.

PRECAUTIONS

DANGER! CAUSES SEVERE EYE AND SKIN BURNS. HARMFUL IF INHALED. HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION.

Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. The product may not be stable under certain conditions of storage or use: high temperature/pressure hazard. Can enter lungs and cause damage. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. Call physician immediately. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. FLOOD and the FLOOD and Paintbrush Design are registered trademarks of PPG Industries, Inc. © 2015 PPG Industries, Inc. All Rights Reserved.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.flood.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
2505, rue de la Métropole,
Longueuil (Québec) Canada J4G 1E5

T.D. FLD138 1/2016

