



All-Purpose Deck Wash

GENERAL DESCRIPTION

All purpose formula for use as a maintenance cleaner for stained or resurfaced decks. Use to clean coated and uncoated wood or composite surfaces. Brighten gray, weathered wood to a refreshed appearance. Will not darken high tannin containing woods such as redwood and cedar.

RECOMMENDED USES

For exterior use only. Use on decks, wood siding, shakes, shingles, and fences. Also recommended for use on composite decking. Test in a small inconspicuous area and let dry before application.

PRODUCT INFORMATION

FLD53

PACKAGING

1 - Gallon (3.78 L)

PRODUCT DATA

PRODUCT TYPE: Oxalic Acid Solution

WEIGHT/GALLON: 8.5 lbs. (3.9 kg) +/- 0.2 lbs. (91 g)

COVERAGE: One gallon (3.78 liters) will clean approximately 250 sq. ft. (23.2 sq. meters). Coverage will vary depending on type, age and texture of wood.

RECOMMENDED SPRAY EQUIPMENT: Use a plastic, pump-style garden sprayer and hose.

CLEANUP: Rinse tools and spray equipment thoroughly with water.

STORAGE: Store in a cool dry location in tightly closed plastic container. Avoid exposure to sunlight. Do not reuse container. Rinse container thoroughly before disposal.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

FEATURES

Ready to use

Cleans and refreshes previously stained decks where the coating is in good condition

Removes stains from mold, mildew and algae

Also for use as a preparation cleaner and brightener for cedar and redwood

All-Purpose Deck Wash

DIRECTIONS FOR INTERIOR AND EXTERIOR USE

AREA PREPARATION: Spray all plants and vegetation liberally with water before and after application. Cover delicate vegetation to avoid damage.

SAFETY PRECAUTIONS: Wear chemical resistant gloves, safety goggles and protective clothing. Do not mix with any other chemicals or other household cleaning products as hazardous fumes may result. Surfaces are slippery when wet. Use caution when walking on wet surfaces during application.

APPLICATION: This product is Ready-To-Use. No dilution is required. Shake well before using. Sweep clean then wet surface with water before applying product. For vertical surfaces, work from bottom to top. Apply product evenly with brush, roller or garden sprayer. Product may damage metal components of spray equipment. Allow product to stand for 20-30 minutes then scrub surface with nylon brush. Make sure to keep surface wet and do not use a wire brush. Rinse surface and adjacent areas using highest pressure from hose. Allow surface to dry 24-48 hours before staining or painting.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITATIONS OF USE

PROTECT FROM FREEZING.

PRECAUTIONS

DANGER! CAUSES RESPIRATORY TRACT, DIGESTIVE TRACT AND EYE BURNS. CAUSES SKIN BURNS. HARMFUL IF SWALLOWED. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. Call physician immediately. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. FLOOD and the FLOOD and Paintbrush Design are registered trademarks of PPG Industries, Inc. © 2015 PPG Industries, Inc. All Rights Reserved.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.flood.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
2505, rue de la Métropole,
Longueuil (Québec) Canada J4G 1E5

T.D. FLD53 1/2016

