



REACTIV LEAF RUST

RUST EFFECT COATING

| | |
|--------------------------------------|--|
| Description | REACTIV LEAF RUST when combined with RUST SPIRIT* creates a natural decorative rust effect on non-ferrous metals and other surfaces by reacting with the metal particles in REACTIV LEAF RUST. |
| Properties | <ul style="list-style-type: none"> • Odourless. • Waterbased. |
| Basic uses | <ul style="list-style-type: none"> • Creating rust effect on all surface types – Glass, Ceramics, Non-ferrous metals.... • Lampshades, Lamp stands, Statues.... • Glass bowls, Tables, Walls, Doors.... |
| Technical characteristics | <p>Finish: Anthracite Reactive Decorative Coating.</p> <p>Vehicle Type: Specific Pigments.</p> <p>Solvent Type: Water.</p> <p>Specific Gravity at 20°C (68°F): 2.03 ± 0.03.</p> <p>Solid Content: 69 ± 3%.</p> <p>Drying Time at 20C (68F) and 50% RH: 6 hours (Minimum).</p> <p>Container Size: 500ml, 2.5Ltr.</p> <p>Shelf Life: 1 year in original, unopened packaging.</p> <p>VOC: EU limit value for this product (cat A/I) 200 g/. (2010). This product contains max 60g/l</p> |
| Good application practice | <p>Cover and protect everything you do not wish to coat.</p> <p>Apply between 5°C and 25°C.</p> <p>Do not apply to hot surfaces.</p> |
| Application tools | <p>Brush.</p> <p>Roller.</p> |
| Surface preparation | <p>Surfaces must be in good sound condition, clean, dry and free of all grease, oil and other surface contamination.</p> <p>Meticulously clean surface using a suitable cleaning agent depending on the substrate and contamination e.g. Acetone, Hot Soapy Water (rinse thoroughly) etc.</p> <p>Non-Porous and Difficult Surfaces (Plastic, Glass, Stainless Steel, Non-Ferrous Metals....) Primer surface with ABSOLUTE PRIMER* prior to using REACTIV LEAF RUST.</p> <p>Surfaces Sensitive to Acids (Woods high in tannin e.g. Oak, Chestnut.... Some Plastics) Primer surface with BLOCKING PRIMER* prior to using REACTIV LEAF RUST.</p> <p>Note: REACTIV LEAF RUST is not required on ferrous surfaces.</p> |
| Application | <p>Use as is. Do not thin.</p> <p>Shake well before use.</p> <p>Apply a generous coat of REACTIV LEAF RUST to cover the surface.</p> <p>Allow to dry.</p> <p>If after drying areas appear not to have enough REACTIV LEAF RUST a 2nd coat may be necessary.</p> <p>Allow to dry.</p> <p>See RUST SPIRIT* Technical Data Sheet for next stage.</p> |
| Additional application advice | Using a brush to apply REACTIV LEAF RUST with a dabbing action allows for a very natural rust effect to be created (see video). |
| Coverage | <p>5m² per litre.</p> <p>Actual coverage will vary depending on application method, type, texture, age, porosity of the surface and the decorative effect desired.</p> |

The information presented here is given for information purposes only and does not engage the liability of the manufacturer, as the application of products is not carried out under its control. * Information on the level of omissions of volatile substances in indoor air, presenting a risk of toxicity through inhalation, on a classification scale ranging from A+ (variable omissions) to C (high omissions).

| | |
|----------------------------|---|
| Clean-up | Soap and water. |
| Storage | Keep from freezing and high temperatures. Store in original container and close lid tightly after use. |
| General information | Every care is taken to ensure that the information provided in this technical data sheet is accurate. Owatrol International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local Owatrol Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the Technical Data Sheet. |
| Safety | Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children. |
| Issue date | November 2017 |

* Same manufacturer

The information presented here is given for information purposes only and does not engage the liability of the manufacturer, as the application of products is not carried out under its control. * Information on the level of omissions of volatile substances in indoor air, presenting a risk of toxicity through inhalation, on a classification scale ranging from A+ (variable omissions) to C (high omissions).

Owatrol Spirit
is a trademark



OWATROL INTERNATIONAL SLU
Barcelona – Spain
Tel. +34 93 125 88 68
Fax +34 93 106 02 13

Find all our solutions:
www.owatrol.com