



Proudly Distributed by: BEST MATERIALS®
Ph: 800-474-7570, 602-272-8128
www.BestMaterials.com
Email: Sales@BestMaterials.com

5587 Stain Block Roof Primer

ETERNA-KOTE®

Silicone Waterproofing Technology

- Use over asphalt roofing
- Keeps top coatings bright white
- Use with Silicone or acrylic coatings
- Blocks bleed through staining
- Improves coverage of top coat

Black Jack® ETERNA-KOTE® Stain Block Primer is a premium stain blocking primer designed to coat over asphalt roofing products. This light gray base coat seals asphalt surfaces, so the top coating maintains color integrity and a brighter finish that delivers maximum reflectivity. Also, this high adhesion formula improves performance and coverage rates of roof coatings. Use prior to **Black Jack® ETERNA-KOTE® Silicone** or **Black Jack® White Elastomeric Roof Coatings**. Waterbased technology is RainSafe in 2 hours, has low odor and easy cleanup.

PREPARATION: Pressure washing entire surface is recommended for best results (use only a wide fan spray tip). All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter. Surfaces with mildew growth or stains must be cleaned with a bleach solution (two parts water to one part bleach). Be certain all surfaces are thoroughly rinsed and dry prior to applying coating. Do Not Thin.

APPLICATION: Surface and air temps must be 50 °F and above for a 24 hour period. Avoid application if heavy dew or rain is expected within 24 hours. Apply on a clear, sunny day in morning hours with a 3/4" nap exterior paint roller or professional airless sprayer. Allow at least 24 hours before applying top coating.

COVERAGE RATE: Approximately 75 - 90 sq.ft. per gallon, depending on surfaces.

NOTE: If roof becomes hot (over 100 °F) during application, it is recommended to delay the project until the next morning when surface is cooler.

CLEAN-UP: Soap and water when wet, or citrus cleaner or mineral spirits when dry.

STORAGE AND HANDLING PRECAUTIONS: DO NOT allow product to freeze. Protective clothing, gloves & eyewear should be used during application. When transporting this product, ensure that lid is tight & pail secure & upright. DO NOT allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. For longest life, store in controlled environment, 35 °F - 80 °F. Do not store in direct sunlight. Close container after use. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility to the roof surface, test a small section first for proper adhesion.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
5587-7-30	5 gal.	12" x 12" x 14.75"	4.75 gal /18 L	54.4 lbs.	1 ea.	027134558757