

ZAR® Interior Oil Base Gold Liquid Leaf Paint

MANUFACTURER

UNITED GILSONITE LABORATORIES


MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.UGL.com



PRODUCT DESCRIPTION

LIQUID LEAF PAINT is an interior oil base gold leaf finish for decorative use where the richness and beauty of gold is desired. Add romantic elegant touch or accent to any surface.

- Brilliant gold leaf-like finish
- Ideal for indoor decorative use such as crafts, picture frames, toys, restoration projects, furniture trim, and more
- Remains stable, will not tarnish in the container

BASIC USES

This one-step, brush-on, long lasting finish is ideal for picture frames, knick-knacks, furniture trim, crafts, etc. Use on wood, metal, glass, ceramics, paper, plaster, or plastic.

LIMITATIONS

FOR INTERIOR USE ONLY.

TECHNICAL DATA

COMPOSITION:

Oil base

% WEIGHT SOLIDS:

44%

% WEIGHT SOLIDS:

20%

DENSITY (LBS./US GAL.):

9.21

VISCOSITY:

25 sec. Ford #4 cup at 77° F

COLOR:

Gold

DRY TIME:

- Recoat 24 hours

Note: Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

CLEAN UP:

Paint thinner or mineral spirits
Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

COVERAGE (SQ. FT.):

100 sq. ft. (9.2m²)/qt.

Note: Actual coverage will vary depending upon application method, surface texture, and porosity.

RECOMMENDED FILM THICKNESS/COAT:

13-21 wet mils/coat

FLASH POINT:

114°F

SHELF LIFE:

5 Years unopened container

FREEZE/THAW:

N/A

CONTAINER SIZES:

One half pint (236 mL) and one quart (946 mL) cans

VOC

Does not exceed 620 g/L

TINTING

N/A

THINNING

Do not thin.

SURFACE PREPARATION

Surface to be painted should be clean and free from all dirt, grease, wax, etc. If your surface has intricate detail areas that show dirt use a scrub brush to get into all the crevices. In some cases your surface may need a white primer for added precaution.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Apply evenly with a good, soft bristle brush. Brush on paint using minimum pressure, making sure the final brush strokes are made toward the previously applied paint. A second coat may be applied after 24 hours drying time. For spraying, reduce 10 percent with pure turpentine.

Allow to dry 24 hours between coats. Temperature, humidity, and film thickness may affect drying time. If while sanding, sandpaper gums or surface feels tacky, extend drying times.

Clean brushes with turpentine. To avoid spontaneous combustion during temporary storage, soak soiled rags and wastes immediately after use in a water-filled closed metal container.

MAINTENANCE

N/A


CAUTION

CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. Keep away from heat



DRY TIME:

Recoat 24 Hours



CLEAN-UP:

Paint Thinner or Mineral Spirits



COVERAGE:

2 Coats



SPREAD RATE:

100 Sq. Ft./Quart

and flame. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose, throat and skin irritation. Overexposure may cause kidney damage. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Close container after use.

Use only with adequate ventilation.

DANGER – RAGS, STEEL WOOL, OR WASTE SOAKED WITH PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call a physician immediately; for skin, wash thoroughly with soap and water. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately. If swallowed, do not induce vomiting. Call a physician immediately.



WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

For additional health and safety information please refer to the "Safety Data Sheet".

ZAR® is a registered trademark of United Gilsonite Laboratories (UGL).



Interior Oil Base
Gold Liquid Leaf Paint
1/2 PT. 6/Case22506
1 QT. 1/Case22512

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.