



# PRODUCT DATA SHEET

Publication Date: 8-31-20

## DRYLOK® Pourable Crack Filler

### PRODUCT DESCRIPTION

DRYLOK® Pourable Masonry Crack Filler is formulated to fill and seal cracks on interior and exterior concrete and masonry surfaces. Reduces radon gas penetration. Dries to the color of concrete.

- Seals and fills cracks in concrete and masonry
- Blends with natural color and texture of surface
- Easy flow formula self-levels
- Reduces radon gas penetration
- Precise nozzle tip - no special tool needed

### BASIC USES

Ideal for interior and exterior concrete and masonry sidewalks, walkways, steps, patios, garage floors, etc.

### TECHNICAL DATA

**COMPOSITION:** Proprietary

**% WEIGHT SOLIDS:** 85%

**COLORS:**

- Gray

**SET TIME:** 12 hours

**COVERAGE:**

One quart (946mL) will fill approximately a 1/4"x 1/2" (6 x 12mm) crack 38 ft (11m) long

Note: Actual coverage will vary depending upon application method, surface texture, and porosity.

**SHELF LIFE:** 2 Years unopened container

**Freeze/Thaw:** Do not freeze

**CONTAINER SIZES:** One quart



#### COVERAGE

fills cracks up to one-half-inch wide and one-quarter-inch deep



#### SET TIME

12 Hours



#### CLEAN-UP

Soap and water

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## DRYLOK® POURABLE CRACK FILLER

### VOC

Does not exceed 40 g/L

### TINTING

N/A

### SURFACE PREPARATION

Apply when air and surface temperatures are a minimum of 50°F (10°C). Crack must be free from frost, dust, dirt, oil, and particles. Wire brushing and hosing facilitates cleaning. Remove excess moisture before filling the crack. Do not apply if rain is expected within 24 hours. SHAKE WELL BEFORE USING. Use only when cracks are 1/2" (12mm) wide or less.

### APPLICATION

Remove the red cap. Cut the tip of the spout to a size slightly smaller than the width of the crack. Squeeze DRYLOK® Pourable Masonry Crack Filler tightly into the crack, over-filling slightly to allow for shrinkage. Smooth patched area with a putty knife. Replace the cap after use.

### VENTILATION

Use only with adequate ventilation.

### CAUTION

**Cancer hazard: Contains Crystalline Silica**, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces, grinding, or spray mists.

**Use only with adequate ventilation.** Do not breathe dust. Harmful if inhaled. Overexposure may cause lung and kidney damage. Avoid contact or prolonged contact with eyes, skin, and clothing. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN.  
DO NOT TAKE INTERNALLY.  
KEEP FROM FREEZING.**

### FIRST AID

In case of eye contact, flush immediately with plenty of water for at least 15 minutes. If swallowed, do not induce vomiting. Call poison control center, hospital emergency room, or physician immediately. If spilled, contain spilled material, and remove with inert absorbent.

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulators.

### WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

⚠ Warning: Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

For additional health and safety information, please refer to the Safety Data Sheet (SDS).


DRYLOK® is a registered trademark of United Gilsonite Laboratories (UGL).

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

## DRYLOK® Pourable Crack Filler

---

	CONTAINER	NUMBER/CASE	COLOR	ORDER NUMBER
DRYLOK® Pourable Crack Filler	1 quart	6/case	Gray	30512



**Gray**

**Note:** Color swatches are representative only.



1-800-845-5227 • Fax 1-570-969-7634 • [www.UGL.com](http://www.UGL.com)

Corporate Office: 1396 Jefferson Avenue, Dunmore, PA 18509

Mail to: P.O. Box 70, Scranton, PA 18501-0070

Plant Locations: Jacksonville, IL • Jackson, MS