

## Technical Data Sheet

<b>PRODUCT</b>	<b>COSMOS LAC SPRAY SILICON LUBE N203</b>
<b>DESCRIPTION/USES</b>	Silicon lube is a high quality multi-purpose mechanical lubricant. Excellent water repellence; ideal for all general and light duty mechanical lubrication purposes Provides long term lubrication any metallic or plastic part.
<b>Viscosity</b>	18-25 sec (Flow Cup DIN4, 20°C)
<b>Density</b>	0.8-0.9 g/L (Density Cup 100cm <sup>3</sup> /20°C, ASTM D – 1475)
<b>VOC content</b>	600 g/L
<b>Flash Point</b>	-104°C (based on propellant)
<b>Drying time</b>	Optimum lubrication is obtained after evaporation of the solvent (Approximately 1 minute).
<b>Color</b>	Transparent
<b>Can Pressure</b>	4bar (20 °C) , 8 bar (50 °C)
<b>Contents</b>	400ml
<b>Application</b>	Remove all dust, rust and oil from the surface. Protect the area which you don't want to be sprayed. Shake the can thoroughly and spray at a distance of 10cm from the surface. Try the spray on testing surface. Apply the silicone spray in a thin layer. Best application temperature: 10°C - 25°C
<b>After use</b>	Spray holding the can inverted for 3". Clean the caps with solvent.
<b>Storage</b>	5-35°C. Do not put in vehicles.