



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : OWATROL RUSTOL DECO DEEP TONE

Product code : rddeept.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint

1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A.: Siège Social.

Address : 2 bis, rue Charles de Gaulle.91070 BONDY.FRANCE.

Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84.

reglementaire@durieu.com

www.durieu.com

1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE:Ireland National Poisons Information Centre: +353 (0) 1 8379964

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Repeated exposure may cause skin dryness or cracking (EUH066).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard statements :

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P260 Do not breathe dust vapours.

P262 Do not get in eyes, on skin, or on clothing.

Precautionary statements - Response :

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Precautionary statements - Disposal :

P501 Dispose of contents / container in a waste collection point.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annex XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification (EC) 1272/2008	Note	%
INDEX: PCP186 CAS: 64742-48-9 EC: 918-481-9 REACH: 01-2119457273-39-XXXX HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	GHS08 Dgr Asp. Tox. 1, H304 EUH:066		25 <= x % < 50
INDEX: 500 CAS: 471-34-1 EC: 207-439-9 REACH: 01-2119486795-18-XXXX		[1]	1 <= x % < 2.5
CARBONATE DE CALCIUM			
INDEX: 315 CAS: 64216-15-5 EC: 264-731-9 REACH: 01-2119978299-15-XXXX	GHS07 Wng Acute Tox. 4, H302 Eye Irrit. 2, H319		1 <= x % < 2.5
CALCIUM ISONONANOATE		[1]	0.1 <= x % < 1
INDEX: 066 CAS: 14808-60-7 EC: 238-878-4			
QUARTZ(SIO2)		[1]	0.1 <= x % < 1
INDEX: 008 CAS: 34590-94-8 EC: 252-104-2 REACH: 01-2119450011-60-XXXX			
(2-METHOXYMETHYLETHOXY)PROPANOL			
INDEX: 061 CAS: 55406-53-6 EC: 259-627-5 REACH: 01-2120762115-60-XXXX 3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC)	GHS06, GHS05, GHS09, GHS08 Dgr Acute Tox. 4, H302 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 3, H331 STOT RE 1, H372 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1		0 <= x % < 0.1
INDEX: 603-053-00-3 CAS: 107-41-5 EC: 203-489-0 REACH: 01-2119539582-35	GHS07 Wng Eye Irrit. 2, H319 Skin Irrit. 2, H315	[1]	0 <= x % < 0.1
2-METHYL PENTANE-2,4-DIOL			
INDEX: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH: 01-2119457435-35	GHS02, GHS07 Wng Flam. Liq. 3, H226 STOT SE 3, H336	[1]	0 <= x % < 0.1
1-METHOXY-2-PROPANOL			
INDEX: 350 CAS: 128-37-0 EC: 204-881-4 REACH: 01-2119565113-46-XXXX	GHS09 Wng Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410	[1]	0 <= x % < 0.1

2,6-DI-TERT-BUTYL-P-CRESOL

M Chronic = 1

Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 061 CAS: 55406-53-6 EC: 259-627-5 REACH: 01-2120762115-60-XXXX		oral: ATE = 1056 mg/kg BW
3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC)		
INDEX: 603-053-00-3 CAS: 107-41-5 EC: 203-489-0 REACH: 01-2119539582-35	Skin Irrit. 2: H315 >=10%	
2-METHYLPENTANE-2,4-DIOL		

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Ce produit n'est pas classé comme inflammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)
- water with AFFF (Aqueous Film Forming Foam) additive

Unsuitable methods of extinction

In the event of a fire, do not use :

- jets d'eau directs

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

Recommended types of packaging :

- Vats

- Drums

Suitable packaging materials :

- Coated steel

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
471-34-1	-	10	-	-	-	-
14808-60-7	-	0.1 A	-	-	-	25
34590-94-8	50	308	-	-	*	84
107-41-5	-	-	25	125	-	84
107-98-2	50	188	100	375	*	84
128-37-0	-	10	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
471-34-1	10 mg/m3	-	-	-	TI
14808-60-7	0.3 mg/m3	-	-	-	R
34590-94-8	50 ppm 308 mg/m ³			Sk	
107-41-5	25 ppm 123 mg/m ³	25 ppm 123 mg/m ³			
107-98-2	100 ppm 375 mg/m ³	150 ppm 560 mg/m ³		Sk	
128-37-0	10 mg/m ³				

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
34590-94-8	308	50	-	-	Peau
107-98-2	375	100	568	150	Peau

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)
- Natural latex
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Suitable type of protective boots :

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category :

- FFP2

Type of mask with combined filters :

Wear a half mask in accordance with standard EN140.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- AX (Brown)

Particle filter according to standard EN143 :

- P2 (White)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state :	Fluid liquid.
------------------	---------------

Colour

Unspecified

Odour

Odour threshold :	Not stated.
-------------------	-------------

Melting point

Melting point/melting range :	Not specified.
-------------------------------	----------------

Freezing point

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------

Boiling point or initial boiling point and boiling range

Boiling point/boiling range :	Not specified.
-------------------------------	----------------

Flammability

Flammability (solid, gas) :	Not stated.
-----------------------------	-------------

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) :	Not stated.
---	-------------

Explosive properties, upper explosivity limit (%) :	Not stated.
---	-------------

Flash point

Flash Point Interval :	60°C < FP <= 93°C
------------------------	-------------------

Auto-ignition temperature

Self-ignition temperature :	Not specified.
-----------------------------	----------------

Decomposition temperature

Decomposition point/decomposition range :	Not specified.
---	----------------

pH

pH (aqueous solution) :	Not stated.
-------------------------	-------------

pH :	Not relevant.
------	---------------

Kinematic viscosity

Viscosity :	v>20.5mm²/s (40°C)
	Method for determining the viscosity : ISO 3104 (Petroleum products - Transparent and opaque liquids - Determination of kinematic viscosity and calculation of dynamic viscosity).

Solubility

Water solubility :	Soluble.
--------------------	----------

Fat solubility :	Not stated.
------------------	-------------

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water :	Not stated.
--	-------------

Vapour pressure

Vapour pressure (50°C) :	Not relevant.
--------------------------	---------------

Density and/or relative density

Density :	> 1
-----------	-----

Relative vapour density

Vapour density :	Not stated.
------------------	-------------

9.2. Other information

VOC (g/l) :	350
-------------	-----

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity :

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Oral route :

LD50 = 1056 mg/kg bodyweight/day

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route :

LD50 > 2000 mg/kg bodyweight/day

Species : Rat

OECD Guideline 402 (Acute Dermal Toxicity)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Oral route :

LD50 > 5000 mg/kg bodyweight/day

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route :

LD50 > 5000 mg/kg bodyweight/day

Species : Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Vapours) :

LC50 > 5000 mg/l

Species : Rat

OECD Guideline 403 (Acute Inhalation Toxicity)

Germ cell mutagenicity :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

No mutagenic effect.

Carcinogenicity :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Carcinogenicity Test : Negative.

No carcinogenic effect.

Reproductive toxicant :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

No toxic effect for reproduction

OECD Guideline 414 (Prenatal Developmental Toxicity Study)

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 128-37-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 14808-60-7 : IARC Group 1 : The agent is carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Fish toxicity : LC50 = 0.067 mg/l

Species : Others

Duration of exposure : 96 h

NOEC = 0.0084 mg/l

Factor M = 1

Species : Pimephales promelas

Duration of exposure : 35 jours

Crustacean toxicity :

EC50 = 0.16 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

EC50 mg/l

Species : Daphnia magna

Duration of exposure : 21 jours

Species : Others

Algae toxicity :

ECr50 = 0.022 mg/l

Species : Scenedesmus subspicatus

Duration of exposure : 72 h

NOEC = 0.0046 mg/l

Factor M = 1

Species : Scenedesmus subspicatus

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Fish toxicity :

LC50 = 1000 mg/l

Species : Oncorhynchus mykiss

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 1000 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

Algae toxicity :

ECr50 = 1000 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Biodegradability : Rapidly degradable.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Octanol/water partition coefficient : log K_{ow} = 2.81

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 * packaging containing residues of or contaminated by dangerous substances

08 01 11 * waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

Container information:

No data available.

Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 350 g/l.

The permitted European levels of VOC in the ready-to-use product (category IIa) are 600 g/l maximum in 2007 and 500 g/l maximum in 2010.

Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.